





SMART SENSOR ELITE PROGRAMMING/DIAGNOSTIC TOOL QUICK START GUIDE





BUTTON FUNCTIONS





- ESC** ESC Key
Press to return to the previous menu.
-  **ENTER** Key
Press to validate or process function.
-  **HOME** Key
Takes you back to MAIN MENU.
-  **POWER ON / OFF**
Turns the tool on and off.
-  **ARROW** Keys
Use these keys to navigate through displayed options.


SELECT VEHICLE

From the MAIN MENU, select  /  , then using the directional arrows, select the **MAKE** /  , **MODEL** /  and **YEAR** /  of the vehicle.

SCAN SENSOR




After selecting the **VEHICLE** to be serviced, select  /  .

Select  /  , if only one sensor is going to be scanned or  /  , if all sensors are going to be scanned.


Position either side of the tool  against the sidewall of the tire near the sensor.

Press  to **SCAN**.

COPY SENSOR

After selecting the **VEHICLE** to be serviced, select . Select , if the original sensor can still be scanned or  to manually enter the original sensor ID.

IF SCAN TO COPY

Press  to scan the original sensor.
Tool displays **ID**.

Press  to **SCAN NEXT** or  /  to **COPY**.






Select **IN CRADLE** or **WIRELESS**.








Place the Smart Sensor in the CRADLE of the tool **or** hold it against the side of the tool  for **WIRELESS**.

Press  to **COPY**.


Note: to wirelessly program a sensor, that is already installed in a tire, first deflate the tire to less than 26 psi, otherwise the sensor can not be programmed.

IF MANUALLY COPY

Use the     to highlight characters and press  to select and **COPY**.



For help identifying the sensor ID, from the **MAIN MENU**, select  /  /  /  , then the **MAKE** /  , **MODEL** /  and **YEAR** / .

Select **IN CRADLE** or **WIRELESS**.


Place the Smart Sensor in the CRADLE of the tool **or** hold it against the side of the tool  for **WIRELESS**.

Press  to **COPY**.

PROGRAM NEW SENSOR

After selecting the **VEHICLE** to be serviced, select  / .


Choose how you want to program the Smart Sensor – **IN CRADLE** or **WIRELESS**.



IF IN CRADLE

Place the Smart Sensor in the cradle of the tool.


IF WIRELESS

Hold the Smart Sensor against the side of the tool .


Press  to **PROGRAM**.

Note: to wirelessly program a sensor, that is already installed in a tire, first deflate the tire to less than 26 psi, otherwise the sensor can not be programmed.

RELEARN

After selecting the **VEHICLE** to be serviced, select  / ←.

Select  / ← to view the **RELEARN PROCEDURE(S)**.

or select  then the appropriate type of relearn (there may only be one), and follow the instructions to **PERFORM** the **RELEARN**.



OBD II OPTIONS

After selecting the **VEHICLE** to be serviced, select  .


Note: If **OBD II OPTIONS**  does not appear, then **OBD II support is not currently available for that vehicle.**

Connect **OBD II Cable** or **Bluetooth Module** to vehicle and press ←.

Note: The **Bluetooth OBD II Module must be paired to the ELITE tool prior to first use.**

To pair the Bluetooth OBD II Module, select **INFORMATION**, then **SETTINGS**, then **OBD II PAIRING**, and following the onscreen instructions.



Note: If **Bluetooth OBD II Modules beeps**, then re-connect **OBD II** by going back to  and press ←.

Select  to upload IDs to vehicle,  to adjust the placard pressures or  to read IDs store in vehicle.

Press ← and follow the onscreen instructions.

UPDATING TOOL

From the MAIN MENU, select  / .

Select **TOOL** or **BLUETOOTH OBD II** to update.

USB PORT

Visit www.tpmsnetwork.com, Create an Account and/or Log In, and download Smart Sensor Updater software.

Load Smart Sensor Updater on to your Windows computer.

Connect tool or Bluetooth OBD II module to computer via included USB Cable

and click .



WIFI

Connect to selected network.

Press  to begin the UPDATE.

NOTE: BLUETOOTH OBD II must be plugged in to vehicle to update wirelessly.

SETTINGS

Select  / .

Using the   to scrool through settings.

Press  to select/change a setting.



Smart Sensor ELITE User Guide
available at www.tpmsnetwork.com

Mobile App for Apple and Android Devices
Visit the App Store and search
TPMS Part Finder



Backed by Industry Leading TPMS Network
24/7 Support • (877) 659-8767 (TPMS)